



Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 12/30/2013 Date of issue: 12/30/2013

Version: 1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE

Product Identifier

Product Name: Pro Star LPC Diesel Fuel Additive

Product Code: 955XX

Intended Use of the Product

Use of the Substance/Mixture: Fuel Additive.

Name, Address, and Telephone of the Responsible Party

Company

Star brite Inc.

4041 SW 47th Avenue

Fort Lauderdale, FL 33314

(954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS

Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 4 H227

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Muta. 1B H340

Carc. 1A H350

STOT SE 3 H336

STOT RE 2 H373

Asp. Tox. 1 H304

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



Signal Word (GHS-US) :

Danger

Hazard Statements (GHS-US) :

H227 - Combustible liquid

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H340 - May cause genetic defects

H350 - May cause cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements (GHS-US) :

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, open flames, sparks - No smoking.

P260 - Do not breathe vapors, spray, mist.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, protective gloves, protective clothing.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P314 - Get medical advice and attention if you feel unwell.
P321 - Specific treatment (see Section 4).
P331 - If swallowed, do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362 - Take off contaminated clothing.
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) for extinction.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Aquatic Chronic 2

H411 - Toxic to aquatic life with long lasting effects

P273 - Avoid release to the environment



Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	60 - 70	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
2-Ethylhexyl nitrate	(CAS No) 27247-96-7	10 - 15	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Aquatic Chronic 2, H411
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	3 - 7 or 5 - 10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Carc. 2, H351 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	3 - 7	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Eye Irrit. 2A, H319 Carc. 2, H351

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

			STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
1,3,5-Trimethylbenzene	(CAS No) 108-67-8	1 - 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	0.1 - 1.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Cumene	(CAS No) 98-82-8	0.1 - 1	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Ethylbenzene	(CAS No) 100-41-4	0.1 - 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Muta. 1B, H340 Carc. 1A, H350 STOT RE 2, H373 Aquatic Acute 2, H401
Naphthalene	(CAS No) 91-20-3	0.1 - 1	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

Additional information: Multiple WHMIS ranges have been listed due to variation in concentration.

SECTION 4: FIRST AID

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Irritation to eyes, skin and respiratory tract. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

Inhalation: May cause drowsiness or dizziness. May cause cancer by inhalation.

Skin Contact: Causes skin irritation. May be harmful in contact with skin.

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Contact: Causes serious eye irritation.

Ingestion: May be fatal if swallowed and enters airways.

Chronic Symptoms: May cause cancer. May cause damage to organs through prolonged or repeated exposure. May cause heritable genetic damage.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIREFIGHTING

Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Reacts with (strong) oxidizers: (increased) risk of fire.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen compounds. Hydrogen cyanide. Formaldehyde.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid all contact with skin, eyes, or clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Eliminate ignition sources. Ventilate area. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters. Dangerous due to potential toxicity for the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s)

Fuel Additive.

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL

Control Parameters

Petroleum distillates, hydrotreated light (64742-47-8)		
British Columbia	OEL TWA (mg/m ³)	200 mg/m ³ (application restricted to conditions in which there are negligible aerosol exposures)
Ethylbenzene (100-41-4)		
Mexico	OEL TWA (mg/m ³)	435 mg/m ³
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m ³)	545 mg/m ³
Mexico	OEL STEL (ppm)	125 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
USA IDLH	US IDLH (ppm)	800 ppm (10% LEL)
Alberta	OEL STEL (mg/m ³)	543 mg/m ³
Alberta	OEL STEL (ppm)	125 ppm
Alberta	OEL TWA (mg/m ³)	434 mg/m ³
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL STEL (mg/m ³)	543 mg/m ³
New Brunswick	OEL STEL (ppm)	125 ppm
New Brunswick	OEL TWA (mg/m ³)	434 mg/m ³
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m ³)	542 mg/m ³
Nunavut	OEL STEL (ppm)	125 ppm
Nunavut	OEL TWA (mg/m ³)	434 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	542 mg/m ³
Northwest Territories	OEL STEL (ppm)	125 ppm
Northwest Territories	OEL TWA (mg/m ³)	434 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Québec	VECD (mg/m ³)	543 mg/m ³
Québec	VECD (ppm)	125 ppm
Québec	VEMP (mg/m ³)	434 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	125 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m ³)	545 mg/m ³
Yukon	OEL STEL (ppm)	125 ppm
Yukon	OEL TWA (mg/m ³)	435 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene, 1,2,4-trimethyl- (95-63-6)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)		
Mexico	OEL TWA (mg/m ³)	435 mg/m ³
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m ³)	655 mg/m ³
Mexico	OEL STEL (ppm)	150 ppm
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Alberta	OEL STEL (mg/m ³)	651 mg/m ³
Alberta	OEL STEL (ppm)	150 ppm
Alberta	OEL TWA (mg/m ³)	434 mg/m ³
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL STEL (ppm)	150 ppm
British Columbia	OEL TWA (ppm)	100 ppm
Manitoba	OEL STEL (ppm)	150 ppm
Manitoba	OEL TWA (ppm)	100 ppm
New Brunswick	OEL STEL (mg/m ³)	651 mg/m ³
New Brunswick	OEL STEL (ppm)	150 ppm
New Brunswick	OEL TWA (mg/m ³)	434 mg/m ³
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL STEL (ppm)	150 ppm
Newfoundland & Labrador	OEL TWA (ppm)	100 ppm
Nova Scotia	OEL STEL (ppm)	150 ppm
Nova Scotia	OEL TWA (ppm)	100 ppm
Nunavut	OEL STEL (mg/m ³)	652 mg/m ³
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m ³)	434 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	652 mg/m ³
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (mg/m ³)	434 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	150 ppm
Ontario	OEL TWA (ppm)	100 ppm
Prince Edward Island	OEL STEL (ppm)	150 ppm
Prince Edward Island	OEL TWA (ppm)	100 ppm
Québec	VECD (mg/m ³)	651 mg/m ³
Québec	VECD (ppm)	150 ppm
Québec	VEMP (mg/m ³)	434 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m ³)	650 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m ³)	435 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cumene (98-82-8)		
Mexico	OEL TWA (mg/m ³)	245 mg/m ³
Mexico	OEL TWA (ppm)	50 ppm
Mexico	OEL STEL (mg/m ³)	365 mg/m ³
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	245 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
USA IDLH	US IDLH (ppm)	900 ppm (10% LEL)
Alberta	OEL TWA (mg/m ³)	246 mg/m ³
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL STEL (ppm)	75 ppm
British Columbia	OEL TWA (ppm)	25 ppm
Manitoba	OEL TWA (ppm)	50 ppm
New Brunswick	OEL TWA (mg/m ³)	246 mg/m ³
New Brunswick	OEL TWA (ppm)	50 ppm
Newfoundland & Labrador	OEL TWA (ppm)	50 ppm
Nova Scotia	OEL TWA (ppm)	50 ppm
Nunavut	OEL STEL (mg/m ³)	370 mg/m ³
Nunavut	OEL STEL (ppm)	75 ppm
Nunavut	OEL TWA (mg/m ³)	245 mg/m ³
Nunavut	OEL TWA (ppm)	50 ppm
Northwest Territories	OEL STEL (mg/m ³)	370 mg/m ³
Northwest Territories	OEL STEL (ppm)	75 ppm
Northwest Territories	OEL TWA (mg/m ³)	245 mg/m ³
Northwest Territories	OEL TWA (ppm)	50 ppm
Ontario	OEL TWA (ppm)	50 ppm
Prince Edward Island	OEL TWA (ppm)	50 ppm
Québec	VEMP (mg/m ³)	246 mg/m ³
Québec	VEMP (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	74 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m ³)	365 mg/m ³
Yukon	OEL STEL (ppm)	75 ppm
Yukon	OEL TWA (mg/m ³)	245 mg/m ³
Yukon	OEL TWA (ppm)	50 ppm
1,3,5-Trimethylbenzene (108-67-8)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
Naphthalene (91-20-3)		
Mexico	OEL TWA (mg/m ³)	50 mg/m ³
Mexico	OEL TWA (ppm)	10 ppm
Mexico	OEL STEL (mg/m ³)	75 mg/m ³
Mexico	OEL STEL (ppm)	15 ppm
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA NIOSH	NIOSH REL (TWA) (mg/m ³)	50 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	75 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	15 ppm
USA IDLH	US IDLH (ppm)	250 ppm
Alberta	OEL STEL (mg/m ³)	79 mg/m ³
Alberta	OEL STEL (ppm)	15 ppm
Alberta	OEL TWA (mg/m ³)	52 mg/m ³
Alberta	OEL TWA (ppm)	10 ppm
British Columbia	OEL STEL (ppm)	15 ppm
British Columbia	OEL TWA (ppm)	10 ppm
Manitoba	OEL STEL (ppm)	15 ppm
Manitoba	OEL TWA (ppm)	10 ppm
New Brunswick	OEL STEL (mg/m ³)	79 mg/m ³
New Brunswick	OEL STEL (ppm)	15 ppm
New Brunswick	OEL TWA (mg/m ³)	52 mg/m ³
New Brunswick	OEL TWA (ppm)	10 ppm
Newfoundland & Labrador	OEL STEL (ppm)	15 ppm
Newfoundland & Labrador	OEL TWA (ppm)	10 ppm
Nova Scotia	OEL STEL (ppm)	15 ppm
Nova Scotia	OEL TWA (ppm)	10 ppm
Nunavut	OEL STEL (mg/m ³)	79 mg/m ³
Nunavut	OEL STEL (ppm)	15 ppm
Nunavut	OEL TWA (mg/m ³)	52 mg/m ³
Nunavut	OEL TWA (ppm)	10 ppm
Northwest Territories	OEL STEL (mg/m ³)	79 mg/m ³
Northwest Territories	OEL STEL (ppm)	15 ppm
Northwest Territories	OEL TWA (mg/m ³)	52 mg/m ³
Northwest Territories	OEL TWA (ppm)	10 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Prince Edward Island	OEL STEL (ppm)	15 ppm
Prince Edward Island	OEL TWA (ppm)	10 ppm
Québec	VECD (mg/m ³)	79 mg/m ³
Québec	VECD (ppm)	15 ppm
Québec	VEMP (mg/m ³)	52 mg/m ³
Québec	VEMP (ppm)	10 ppm
Saskatchewan	OEL STEL (ppm)	15 ppm
Saskatchewan	OEL TWA (ppm)	10 ppm
Yukon	OEL STEL (mg/m ³)	75 mg/m ³
Yukon	OEL STEL (ppm)	15 ppm
Yukon	OEL TWA (mg/m ³)	50 mg/m ³
Yukon	OEL TWA (ppm)	10 ppm

Exposure Controls


Appropriate Engineering Controls: Ensure all national/local regulations are observed. Use explosion-proof equipment. Take precautionary measures against static discharges. Gas detectors should be used when flammable gases/vapours may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal Protective Equipment: Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Wear fire/flammable resistant/retardant clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Consumer Exposure Controls: Do not eat, drink or smoke during use

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Colorless
Odor	: Characteristic
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: > 100 °C (212 °F)
Flash Point	: 70 °C (158 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: 1.097 (water = 1) at 20 °C (68 °F)
Specific Gravity	: 1.097 at 20 °C (68 °F)
Solubility	: Insoluble.
Log Pow	: Not available
Log Kow	: Not available
Viscosity, Kinematic	: Not available
Viscosity, Dynamic	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Not available

SECTION 10: STABILITY AND

Reactivity: Reacts with (strong) oxidizers: (increased) risk of fire.

Chemical Stability: Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Nitrogen compounds. Hydrogen cyanide. Formaldehyde.

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: TOXICOLOGICAL

Information on Toxicological Effects - Product

Acute Toxicity : Not classified
LD50 and LC50 Data Not available
Skin Corrosion/Irritation: Causes skin irritation.
Serious Eye Damage/Irritation: Causes serious eye irritation.
Respiratory or Skin Sensitization: Not classified
Germ Cell Mutagenicity: May cause genetic defects.
Teratogenicity: Not available
Carcinogenicity: May cause cancer.
Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.
Reproductive Toxicity: Not classified
Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.
Aspiration Hazard: May be fatal if swallowed and enters airways.
Symptoms/Injuries After Inhalation: May cause drowsiness or dizziness. May cause cancer by inhalation.
Symptoms/Injuries After Skin Contact: Causes skin irritation. May be harmful in contact with skin.
Symptoms/Injuries After Eye Contact: Causes serious eye irritation.
Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways.
Chronic Symptoms: May cause cancer. May cause damage to organs through prolonged or repeated exposure. May cause heritable genetic damage.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat (mg/l)	> 5.2 mg/l/4h
2-Ethylhexyl nitrate (27247-96-7)	
ATE (oral)	500.000 mg/kg body weight
ATE (dermal)	1100.000 mg/kg body weight
ATE (vapors)	11.000 mg/l/4h
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2 ml/kg
LC50 Inhalation Rat (mg/l)	> 590 mg/m ³ (Exposure time: 4 h)
Ethylbenzene (100-41-4)	
LD50 Oral Rat	3500 mg/kg
LD50 Dermal Rabbit	15354 mg/kg
LC50 Inhalation Rat (mg/l)	17.2 mg/l/4h (Exposure time: 4 h)
ATE (oral)	3500.000 mg/kg body weight
ATE (dermal)	15354.000 mg/kg body weight
ATE (vapors)	17.200 mg/l/4h
ATE (dust, mist)	17.200 mg/l/4h
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 Oral Rat	6000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat (mg/l)	18 g/m ³ (Exposure time: 4 h)
ATE (oral)	6000.000 mg/kg body weight
ATE (vapors)	10.800 mg/l/4h
ATE (dust, mist)	18.000 mg/l/4h

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 Oral Rat	4300 mg/kg
LC50 Inhalation Rat (mg/l)	47635 mg/l/4h (Exposure time: 4 h)
LC50 Inhalation Rat (ppm)	6247 ppm/4h (species: Sprague-Dawley)
ATE (oral)	4300.000 mg/kg body weight
ATE (dermal)	1100.000 mg/kg body weight
ATE (vapors)	11.000 mg/l/4h

Cumene (98-82-8)	
LD50 Oral Rat	2260 mg/kg
LD50 Dermal Rabbit	10000 mg/kg
ATE (oral)	2260.000 mg/kg body weight
ATE (dermal)	10000.000 mg/kg body weight

1,3,5-Trimethylbenzene (108-67-8)	
LC50 Inhalation Rat (mg/l)	24 g/m ³ (Exposure time: 4 h)
ATE (vapors)	24.000 mg/l/4h
ATE (dust, mist)	24.000 mg/l/4h

Naphthalene (91-20-3)	
LD50 Oral Rat	533 - 710 mg/kg
LD50 Dermal Rabbit	> 20 g/kg
LC50 Inhalation Rat (mg/l)	> 340 mg/m ³ (Exposure time: 1 h)
ATE (oral)	533.000 mg/kg body weight

Ethylbenzene (100-41-4)	
IARC Group	2B
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC Group	3

Cumene (98-82-8)	
IARC Group	2B
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

Naphthalene (91-20-3)	
IARC Group	2B
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human Carcinogen.

SECTION 12: ECOLOGICAL

Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects.

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LC50 Fish 1	19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

Ethylbenzene (100-41-4)	
LC50 Fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	4.6 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
LC 50 Fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EC50 Other Aquatic Organisms 2	> 438 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
Benzene, 1,2,4-trimethyl- (95-63-6)	
LC50 Fish 1	7.19 - 8.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 Fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC 50 Fish 2	2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	(Exposure time: 48 h - Species: Gammarus lacustris)
Cumene (98-82-8)	
LC50 Fish 1	6.04 - 6.61 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	2.6 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
LC 50 Fish 2	4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	7.9 - 14.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
1,3,5-Trimethylbenzene (108-67-8)	
LC50 Fish 1	3.48 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
Naphthalene (91-20-3)	
LC50 Fish 1	5.74 - 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
<u>Persistence and Degradability</u>	
Pro Star LPC Diesel Fuel Additive	
Persistence and Degradability	Not established.
<u>Bioaccumulative Potential</u>	
Pro Star LPC Diesel Fuel Additive	
Bioaccumulative Potential	Not established.
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF fish 1	61 - 159
2-Ethylhexyl nitrate (27247-96-7)	
Log Pow	4.14
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
BCF fish 1	61 - 159
Log Pow	2.9 - 6.1
Ethylbenzene (100-41-4)	
BCF fish 1	15
Log Pow	3.118
Benzene, 1,2,4-trimethyl- (95-63-6)	
Log Pow	3.63
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0.6 (0.6 - 15)
Log Pow	2.77 - 3.15
Cumene (98-82-8)	
BCF fish 1	35.5
Log Pow	3.55 (at 23 °C)
Naphthalene (91-20-3)	
BCF fish 1	30 - 430

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Log Pow	3.3 (at 20 °C)
---------	----------------

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology – Waste Materials: Hazardous waste due to toxicity.

SECTION 14: TRANSPORT

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number

DOT NA no. : NA1993

UN-No. (TDG) : UN3082

UN-No. (IMDG) : 3082

UN-No.(IATA) : 3082

UN Proper Shipping Name

Proper Shipping Name (DOT) : COMBUSTIBLE LIQUID, N.O.S. Contains petroleum distillates, kerosine, and morpholine

Proper Shipping Name (TDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Petroleum distillates, hydrotreated light)

Proper Shipping Name (IATA) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Petroleum distillates, hydrotreated light)

Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Petroleum distillates, hydrotreated light)

Transport Document Description (DOT) : NA1993 COMBUSTIBLE LIQUID, N.O.S. (CONTAINS PETROLEUM DISTILLATES, KEROSENE, AND MORPHOLINE), 3, III, Marine Pollutant

Transport Document Description (TDG) : UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((2- Ethylhexyl)-nitrate; Hydrocarbons, C10, aromatics, <1% naphthalene.), 9, III, Marine Pollutant

Transport Document Description (ADR) (IMDG/IATA) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((2- Ethylhexyl)-nitrate; Hydrocarbons, C10, aromatics, <1% naphthalene), 9, III, Marine Pollutant, (E)

Transport Hazard Class(es)

Department Of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

DOT Symbols : D - Proper shipping name for domestic use only, G - Identifies PSN requiring a technical name

Packing Group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2).
Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 Cfr 173.xxx) : 150

DOT Packaging Non Bulk (49 Cfr 173.xxx) : 203

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Bulk (49 Cfr 173.xxx) : 241
TDG Primary Hazard Classes : 9 - Class 9 - Miscellaneous Products, Substances or Organisms
Hazard Labels (TDG) : 9 - Miscellaneous dangerous compounds



Packing Group (TDG) : III - Minor Danger
TDG Special Provisions : 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks.
2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act".

Explosive Limit And Limited Quantity Index : 5
Marine Pollutant : P
Class (IMDG) : 9
Danger Labels (IMDG) : 9



Packing Group (IMDG) : III
Class (IATA) : 9

Hazard Labels (IATA) : 9



Packing Group (IATA) : III - Minor Danger
Marine Pollutant : P



Additional Information

Emergency Response Guide (ERG) Number : 128
Other Information : This product meets the limited quantities exception as follows: DOT: Not regulated as dangerous goods except when shipped in bulk. Otherwise, the above descriptions apply.

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Overland transport Regulated by DOT as NA1993 Combustible liquid, n.o.s. ((2-Ethylhexyl)-nitrate; Hydrocarbons, C10, aromatics, <1% naphthalene)

Transport by sea

Dot Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Special Provisions (IMDG) : 274,335

Excepted Quantities (IMDG) : E1

IBC Packing Instructions (IMDG) : IBC03

Packing Instructions (IMDG) : P001,LP01

Packing Provisions (IMDG) : PP1

Tank Instructions (IMDG) : T4

Tank Special Provisions (IMDG) : TP2,TP29

Stowage Category (IMDG) : A

MFAG-NO : 171

Marine Pollutant : Yes

Air transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75) : 220 L

CAO Packing Instructions (IATA) : 964

CAO Max Net Quantity (IATA) : 450L

PCA Packing Instructions (IATA) : 964

PCA Limited Quantities (IATA) : Y964

PCA Limited Quantity Max Net Quantity (IATA) : 30kgG

PCA Max Net Quantity (IATA) : 450L

PCA Excepted Quantities (IATA) : E1

CAO Max Net Quantity (IATA) : 450L

CAO Packing Instructions (IATA) : 964

Special Provision (IATA) : A97,A158

Erg Code (IATA) : 9L

SECTION 15: REGULATORY

US Federal Regulations

Pro Star LPC Diesel Fuel Additive	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
Petroleum distillates, hydrotreated light (64742-47-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2-Ethylhexyl nitrate (27247-96-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Ethylbenzene (100-41-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1.0 %

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	100 lb
SARA Section 313 - Emission Reporting	1.0 %
Cumene (98-82-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %
1,3,5-Trimethylbenzene (108-67-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Naphthalene (91-20-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	100 lb
SARA Section 313 - Emission Reporting	0.1 %
<u>US State Regulations</u>	
Ethylbenzene (100-41-4)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Cumene (98-82-8)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Naphthalene (91-20-3)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Petroleum distillates, hydrotreated light (64742-47-8)	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
2-Ethylhexyl nitrate (27247-96-7)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Ethylbenzene (100-41-4)	
U.S. - California - Priority Toxic Pollutants - Human Health Criteria	
U.S. - California - SCAQMD - Toxic Air Contaminants - Carcinogens	
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic	
U.S. - California - SDAPCD - Toxic Air Contaminants - Carcinogenic Impacts Must Be Calculated	
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)	
U.S. - Colorado - Groundwater Quality Standards	
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Level Goals (MCLGs)	

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Levels (MCLs)
U.S. - Connecticut - Drinking Water Quality Standards - Maximum Contaminant Levels
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Connecticut - Water Quality Standards - Consumption of Organisms Only
U.S. - Connecticut - Water Quality Standards - Consumption of Water and Organisms
U.S. - Connecticut - Water Quality Standards - Health Designations
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Florida - Drinking Water Standards - Volatile Organic Contaminants - Maximum Contaminant Levels (MCLs)
U.S. - Georgia - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminant Carcinogens
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Maryland - Surface Water Quality Standards - Consumption of Organisms Only
U.S. - Maryland - Surface Water Quality Standards - Consumption of Water and Organisms
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELS)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - Missouri - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Nebraska - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New Mexico - Water Quality - Standards for Ground Water of 10,000 mg/L TDS Concentration or Less
U.S. - New York - Occupational Exposure Limits - TWAs

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Air Pollutants - Unit Risk Factors
U.S. - North Dakota - Water Quality Standards - Human Health Value for Class III
U.S. - North Dakota - Water Quality Standards - Human Health Value for Classes I, IA, II
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Chronic Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Human Health Criteria for Consumption of Aquatic Organisms Only
U.S. - Rhode Island - Water Quality Standards - Human Health Criteria for Consumption of Water and Aquatic Organisms
U.S. - South Carolina - Maximum Contaminant Levels (MCLs)
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Drinking Water Standards - Maximum Contaminant Levels (MCLs)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Utah - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Virginia - Water Quality Standards - Public Water Supply Effluent Limits
U.S. - Virginia - Water Quality Standards - Surface Waters Not Used for the Public Water Supply Effluent Limits
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - West Virginia - Water Quality - Groundwater Standards - Ceiling Concentrations
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Benzene, 1,2,4-trimethyl- (95-63-6)

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Georgia - Drinking Water - Unregulated Volatile Organic Contaminants
U.S. - Illinois - Toxic Air Contaminants
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Minnesota - Hazardous Substance List
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Groundwater Quality Standards
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Level Goals (MCLGs)
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Levels (MCLs)
U.S. - Connecticut - Drinking Water Quality Standards - Maximum Contaminant Levels
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Florida - Drinking Water Standards - Volatile Organic Contaminants - Maximum Contaminant Levels (MCLs)
U.S. - Georgia - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELS)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - Missouri - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Nebraska - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New Mexico - Water Quality - Standards for Ground Water of 10,000 mg/L TDS Concentration or Less
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Carolina - Control of Toxic Air Pollutants
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - North Dakota - Water Quality Standards - Human Health Value for Classes I, IA, II
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Chronic Freshwater Aquatic Life Criteria
U.S. - South Carolina - Maximum Contaminant Levels (MCLs)
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Drinking Water Standards - Maximum Contaminant Levels (MCLs)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Utah - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - West Virginia - Water Quality - Groundwater Standards - Ceiling Concentrations
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Cumene (98-82-8)

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Georgia - Drinking Water - Unregulated Volatile Organic Contaminants
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminant Carcinogens
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - Skin Designations
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New York - Occupational Exposure Limits - Skin Designations
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Oregon - Permissible Exposure Limits - Skin Designations
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - Skin Designations
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - Skin Designations
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

1,3,5-Trimethylbenzene (108-67-8)

U.S. - Georgia - Drinking Water - Unregulated Volatile Organic Contaminants

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Naphthalene (91-20-3)

U.S. - California - SCAQMD - Toxic Air Contaminants - Carcinogens
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - SDAPCD - Toxic Air Contaminants - Carcinogenic Impacts Must Be Calculated
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Groundwater Quality Standards
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Connecticut - Water Quality Standards - Consumption of Organisms Only
U.S. - Connecticut - Water Quality Standards - Consumption of Water and Organisms
U.S. - Connecticut - Water Quality Standards - Health Designations
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Georgia - Drinking Water - Unregulated Volatile Organic Contaminants
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminant Carcinogens
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water Guidelines
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELS)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Priority Chemical Avoidance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Air Pollutants - Unit Risk Factors
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Chronic Freshwater Aquatic Life Criteria
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Hazardous Waste - Hazardous Constituents
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Dangerous Waste - Dangerous Waste Constituents List
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Canadian Regulations

Pro Star LPC Diesel Fuel Additive

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--



Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
2-Ethylhexyl nitrate (27247-96-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Ethylbenzene (100-41-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Cumene (98-82-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
1,3,5-Trimethylbenzene (108-67-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 3 - Combustible Liquid
Naphthalene (91-20-3)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 4 - Flammable Solid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

SECTION 16: OTHER

Revision date : 12/30/2013
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1


Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

- NFPA Health Hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- NFPA Fire Hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
- NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Party Responsible for the Preparation of This Document

Starbrite®

Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

Pro Star LPC Diesel Fuel Additive

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

North America GHS US 2012 & WHMIS