

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: +01-813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** PERMA POXY MULTI-METAL EPOXY STICK 56G  
**Item No:** 84309  
**Product Type:** Epoxy resin

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
MAGNESIUM SILICATE 14807-96-6	30-60	2 mg/m <sup>3</sup>	20 mppcf
IRON 7439-89-6	10-30	Not listed	Not listed
GLASS OXIDE 65997-17-3	10-30	Not listed	Not listed
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	<10	Not listed	Not listed
MERCAPTAN AMINE BLEND MIXTURE	<10	Not listed	Not listed
ALUMINUM OXIDE 1344-28-1	<5	Not listed	15 mg/m <sup>3</sup>
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
SILICA, QUARTZ 14808-60-7	0.1-1.0	0.025 mg/m <sup>3</sup>	Not listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye and skin irritation. May cause skin sensitization. May be harmful if swallowed.  
**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation  
**Signs and Symptoms of Exposure:** Ingestion may cause nausea and vomiting. Overexposure may cause eye and skin redness. Repeated skin contact may cause allergic skin reactions.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
MAGNESIUM SILICATE 14807-96-6	30-60	male rat-some evidence, female rat-clear evidence, male mice-no evidence, female mice-no evidence	A4-Not classifiable as a human carcinogen	Group 3 Supplement 7, 1987 Monograph 42, 1987
ALUMINUM OXIDE 1344-28-1	<5		A4 Not classifiable as a human carcinogen	
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	male rat-negative, female rat-negative, male mice-negative, female mice-negative	A4	Group 2B; Vol 93,2006; Vol 47,1989
SILICA, QUARTZ 14808-60-7	0.1-1.0		A2 - Suspected Human Carcinogen	Group 1; Monograph 68, 1997

**Medical Conditions Recognized as Being Aggravated by Exposure:** Preexisting skin disorders.

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

#### 4. FIRST AID MEASURES

**Skin Contact:** Wash off with soap and water. If skin irritation persists, call a physician.  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** >200 F PMCC  
**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.  
**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact  
**Hazardous Products of Combustion:** Oxides of carbon, Oxides of nitrogen, Ammonia, Oxides of sulfur, Aldehydes  
**Unusual Fire/Explosion Hazards:** None.  
**Lower Explosive Limit:** Not determined.  
**Upper Explosive Limit:** Not determined.

#### 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Maintain good ventilation. Scrape up putty and place in an appropriate waste container for disposal.

#### 7. HANDLING AND STORAGE

**Storage:** Store in a cool, dry area.  
**Handling:** Avoid contact with skin and eyes. Discard contaminated leather gloves and shoes. Wash thoroughly with soap and water after handling.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eyes:** Safety glasses.  
**Skin:** Neoprene or nitrile gloves recommended.  
**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.  
**Respiratory Protection:** An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Black putty  
**Odor:** Slight  
**Boiling Point:** >500°F  
**pH:** Does not apply  
**Solubility in Water:** Negligible  
**Specific Gravity:** 1.1  
**VOC(Wt.%):** 0  
**Vapor Pressure:** <1 mmHg @ 70°F  
**Vapor Density (Air=1):** >1  
**Evaporation Rate:** <1 (butyl acetate = 1)

#### 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable  
**Hazardous Polymerization:** Will not occur  
**Incompatibilities:** Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines), Sodium/calcium hypochlorite  
**Conditions to Avoid:** Heat.  
**Hazardous Products of Combustion:** Oxides of carbon, Oxides of nitrogen, Ammonia, Oxides of sulfur, Aldehydes

#### 11. TOXICOLOGICAL INFORMATION

See Section 3

#### 12. ECOLOGICAL INFORMATION

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

## 14. TRANSPORTATION INFORMATION

### DOT (49CFR 172)

#### Ground Transport (DOT)

**DOT Shipping Name:** Not Regulated  
**Hazard Class:** None  
**UN/ID Number:** None

#### IATA

**Proper Shipping Name:** Not regulated  
**Class or Division:** None  
**UN/ID Number:** None

#### IMDG

**Proper Shipping:** Not regulated  
**Hazard Class:** None  
**UN Number:** None

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

None

**California Proposition 65:** WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 1, REACTIVITY 1.

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** February 26, 2009

**Revision Number:** 4

**Telephone No.:** 1-87-Permatex (877) 376-2839